

Simplex/Duplex (Zipcord), 62.5/125 Multimode, 3.0mm

Precision Fiber Products standard 3.0mm Simplex and Duplex cables are designed for the termination of the industry standard connectors. This cable is optimized for the cable termination process. Available with Corning's Standard SMF-28e+™ Optical Gigabit Fiber or InfiniCor® Gigabit Fibers, or other fibers to meet your particular application. All Cables are available in Riser (OFNR), Plenum (OFNP), or LSZH jackets. All Riser and Plenum cable are RoHS compliant.

Product Specifications

Buffer Size (um)	900
Storage Temp (C)	-40 / +85
Operating Temp (C)	-20 / +85



Jacket Characteristics

Jacket Material	Fiber Count	Diameter (mm)	Weight (lbs/km)	Pull Load (N) Install/Operate	Bend Radius (cm) Install/Operate
Riser, Orange, RoHS	1	2.9	13	400/100	6/3
Plenum, Orange, RoHS	1	2.9	13	400/100	6/3
LSZH, Orange, RoHS	1	2.9	13	400/100	6/3
Riser, Orange, RoHS	2	2.9 x 5.8	25.5	400/100	6/3
Plenum, Orange, RoHS	2	2.9 x 5.8	25.5	400/100	6/3
LSZH, Orange, RoHS	2	2.9 x 5.8	25.5	400/100	6/3

Optical Characteristics

Mode	Core/Clad	Numerical Aperture	Typ. Atten. (dB/km)	Max. Atten. (dB/km)	Bandwidth (Mhz*km) / Corning#
Multimode	62.5/125	.275	3.0 / 1.0	3.75 / 1.5	220/500 InfiniCor® 300 optical fiber 385/500 InfiniCor® CL™ 1000 optical fiber